


Prestige Elite



Notified Body 0497
n°1765/07

General description: asphalt shingle with copper



bituminous compound	-		Blown bitumen	
length	EN 544	mm	1000	+/-3
width	EN 544	mm	340	+/-3
thickness	-	mm	4,7	+/-10%
exposed area	-	mm	145	-
copper thickness	-	µm	70	+/-3

Physical-chemical properties

weight	-	kg/m ²	16,6	+/-8%
mass of the fibreglass mat	-	g/m ²	2*80	+/-10%
bitumen single layer	EN 544	g/m ²	>3400	-
mechanical resistance MD/CMD	EN 544	%	1500/1500	+/-15%
nail resistance	EN 544	N	>200	-
peeling	EN 544	N/cm	>5	-

Fire behaviour

classification according	EN 13501-5	B roof (t1)
classification according	EN 13501-1	C s2 d0

Wrapping

type	cartboard
shingles for bundle	14
m ² /bundle	2,03
m ² /pallet	97,44

Further info about company, product and roofing instruction on web site www.tegola canadese.com

Tegola Canadese S.p.A.
Via dell'Industria, 21- 31029 Vittorio V.to (TV) - I -
Tel. +39.0438.9111 - Fax +39.0438.911260
e-mail: info@tegolacanadese.com



Company certified according quality system ISO 9001 and environmental system ISO14001